



SYNMAX™ SYNTHETIC RACING OIL SAE 5W-50

Material Safety Data Sheet - Prepared According to OSHA Hazard Communication Standard 29CFR 1910.1200
Page 1 of 9 MSDS # 640550108 - Effective Date: 1JAN2009

MATERIAL SAFETY DATA SHEET

SECTION 1 PRODUCT AND COMPANY IDENTIFICATION

Product:

Product Name: SYNMAX™ SYNTHETIC RACING OIL SAE 5W-50
Product Description: Synthetic Base Stocks and Additives
Product Code: 640550
MSDS Number: 640550108
Intended Use: Competition Race Engine Oil – Professional Use Only.

Company Identification:

Manufacturer: TITAN PERFORMANCE PRODUCTS, LLC.
Address: 13750 METRIC DRIVE
ROSCOE, ILLINOIS 61073 USA
Company Phone: (815) 389-9999
Internet Address: <http://www.synmaxperformancelubricants.com>

SECTION 2 PRODUCT INGREDIENT COMPOSITION

Reportable Hazardous Substance(s) or Complex Substance(s)

Name	CAS#	Concentration*
Synthetic Motor Oil		
Synthetic Hydrocarbon Base Oil	Mixture	80-85% weight
Proprietary Additives	Mixture	15-19% weight
Zinc Dithiophosphate	68649-42-3	< 1-2 % weight

* All concentrations are percent by weight unless material is a gas.

CAS Number: Not applicable for mixtures.

Hazardous Ingredients: This material has no known hazards under applicable laws.
This material is not considered hazardous by the OSHA Hazard Communication Standard 29CFR 1910.1200

See Section(s) 9, 11, 17 for complete health hazard information.

SECTION 3 STABILITY AND REACTIVITY

Stability: Material is stable under normal conditions.
Conditions to Avoid: Excessive heat. High energy sources of ignition.
Materials to Avoid: Strong oxidizers
Hazardous
Decomposition Products: Material does not decompose at ambient temperatures.
Hazardous Polymerization: Will not occur.



SYNMAX™ SYNTHETIC RACING OIL SAE 5W-50

Material Safety Data Sheet - Prepared According to OSHA Hazard Communication Standard 29CFR 1910.1200
Page 3 of 9 MSDS # 640550108 - Effective Date: 1JAN2009

Extinguishing Media

Appropriate Media: Use water fog, foam, dry chemical or carbon dioxide (CO2) to extinguish flames.

Inappropriate Media: Straight Streams of Water

Fire Fighting Instructions: Evacuate area. Prevent runoff from fire control or dilution from entering streams, sewers, or drinking water supply. Firefighters should use standard protective equipment and in enclosed spaces, self-contained breathing apparatus (SCBA). Use water spray to cool fire exposed surfaces and to protect personnel.

Hazardous Combustion Products: Sulfur oxides, Smoke, Fume, Oxides of carbon, incomplete combustion products, Aldehydes. Note: Material may ignite when preheated.

SECTION 7

ACCIDENTAL RELEASE MEASURES

Proactive Measures: Wear appropriate personal protective equipment when cleaning spills. May burn although not readily ignitable.

Notification Procedures: In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations. In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations. US regulations require reporting releases of this material to the environment which exceed the applicable reportable quantity or oil spills which could reach any waterway including intermittent dry creeks. National Response Center can be reached at (800)424-8802.

Spill Management: FOR LARGE SPILLS: Dike far ahead of liquid spill for later recovery and disposal. Prevent entry into waterways, sewers, basements or confined areas. Remove with vacuum truck or pump to storage/salvage vessel/container. FOR SMALL SPILLS: soak up residue with an absorbent such as clay, sand or suitable material. Place in a non-leaking container and seal tightly for proper disposal. PLACE IN CONTAINER FOR PROPER DISPOSAL.

Reporting: CERCLA: Product is covered by EPA's Comprehensive Environmental Response, Compensation and Liability Act. (CERCLA) petroleum exclusion. Releases to air, land or water are not reportable under CERCLA (Superfund).

Clean Water Act: This product is oil as defined under section 311 of EPA's Clean Water Act (CWA). Spills into to leading to Surface waters that cause sheen, must be reported to the National Response Center 1-800-424-8802

SECTION 8

HANDLING AND STORAGE

Pumping Temperature: Not Determined. **Loading Temperature:** Not Determined.

Handling Maximum Temp: Not Determined. **Storage Maximum Temp:** Not Determined.

Storage Procedures: Do not store in open or unlabelled containers.

Handling Procedures: Avoid contact with used product. Prevent small spills and leakage to avoid slip hazard.

Keep containers closed when not in use. Wash thoroughly after handling. Empty container, contains product residue which may exhibit hazards of product.



SYNMAX™ SYNTHETIC RACING OIL SAE 5W-50

Material Safety Data Sheet - Prepared According to OSHA Hazard Communication Standard 22CFR 1910.1200
Page 4 of 9 MSDS # 640550108 - Effective Date: 1JAN2009

SECTION 9

EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Limits:	None established.
Other Exposure Limits:	Contains mineral oil. Under conditions which may generate mists, When mists /aerosols can occur, the following are recommended: 5 mg/m ³ - ACGIH TLV, 10 mg/m ³ - ACGIH STEL, 5 mg/m ³ - OSHA PEL.
Engineering/Ventilation:	If use generates a mist or vapor, local exhaust ventilation is recommended.
Respiratory Protection:	Under normal use conditions, respirator is not usually required. Use NIOSH/MSHA Approved disposable dust/mist mask if the recommended exposure limit is exceeded. Use self-contained breathing apparatus for entry into confined space, for other poorly ventilated areas and for large spill clean-up sites.
Clothing Recommendations:	Long sleeve shirt is recommended, Launder contaminated clothing after use. Do not wear rings, watches or similar apparel that could entrap the material and cause a skin reaction. In accordance with good industrial hygiene practices, precautions should be taken to avoid skin contact.
Eye Protection:	When eye contact may occur, safety glasses with side shields or splash goggles.
Skin and Body Protection:	No skin protection is ordinarily required under normal conditions of use.
Hand Protection:	No protection is ordinarily required under normal conditions of use. Any specific glove information provided is based on published literature and glove manufacturer data. Work conditions can greatly affect glove durability; inspect and replace worn or damaged gloves. Types to be considered include Oil or chemical resistant gloves.
Specific Hygiene Measures:	Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned. Practice good housekeeping.

NOTE: Limits/standards shown for guidance only. Follow applicable regulations.

Environmental Controls: See Sections 7, 8, 13, 14.

SECTION 10

PHYSICAL AND CHEMICAL PROPERTIES

Typical physical and chemical properties are given below.
Consult the Supplier in Section 1 for additional data.

GENERAL INFORMATION

Viscosity:	146 Centistokes (40°C) 21 Centistokes (100°C)	Appearance:	Dark Blue Green Liquid.
Specific Gravity:	0.85 (15.6°C)	Odor Threshold:	Unknown
Bulk Density:	Not determined.	Lower Flammability:	Not determined.
Flash Point:	227°C, 440°F PMCC (Typical)	Water Solubility:	Insoluble.
Boiling Point:	Not determined.		
Pour Point Temperature:	-41°C, -42°F		
Melting/Freezing Point:	Not determined.		
Physical State:	Liquid		
Odor:	Mild Petroleum Odor		
Upper Flammability:	Not determined.		
Auto-Ignition point:	Not determined.		



SYNMAX™ SYNTHETIC RACING OIL SAE 5W-50

Material Safety Data Sheet - Prepared According to OSHA Hazard Communication Standard 29CFR 1910.1200
Page 5 of 9 MSDS # 640550108 - Effective Date: 1JAN2009

PH:	Not determined.	Percent Solid:	Not determined.
Percent Volatile:	Unknown.	Percent VOC:	Not determined.
Vapor Density:	Not determined.	Evaporation Rate:	Not determined.
Explosion Data:	Material does not have explosive properties		

SECTION 11 TOXICOLOGICAL INFORMATION

-ACCUTE EXPOSURE -

Skin Irritation:	May cause skin irritation, based on data from components or similar materials. Not expected to meet EU R38 criteria. Prolonged or repeated skin contact as from clothing wet with material may cause dermatitis. Symptoms may include redness, edema, drying and cracking of the skin
Eye Irritation:	May cause eye irritation. Does not meet Canadian D2B or EU criteria. Based on data from components or similar materials.
Respiratory Irritation:	If material is misted or if vapors are generated from heating, exposure may cause irritation of the mucous membranes and the upper respiratory tract. Based on data for components and similar materials.
Dermal Toxicity:	The LD50 is >2000mg/Kg. Based on data from components or similar materials.
Inhalation Toxicity:	No data available to indicate components may be a toxic inhalation hazard.
Oral Toxicity:	The LD50 in rats is >5000mg/kg. Based on data from components or similar materials. Material can be aspirated into the lungs during the act of swallowing or vomiting. This could result in sever injury to the lungs and death.
Dermal Sensitization:	No data available to indicate product or components may be a skin sensitization.
Inhalation Sensitization:	No data available to indicate components may be a respiratory sensitization.

-CHRONIC EXPOSURE-

Chronic Toxicity:	No data available to indicate product or components presents greater than 1% are chronic health hazards.
Carcinogenicity:	This product is formulated with mineral oils which are considered to be severely refined and not considered to be carcinogenic under IARC. All of the oils in this product have been demonstrated to contain less than 2.5% extractables by the IP 346 test.
Mutagenicity:	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.
Reproductive Toxicity:	No data available to indicate product or any components present at greater than 0.1% that may cause reproductive toxicity.
Teratogenicity:	No data available to indicate product or any components present at greater than 0.1% may cause birth defects.

-ADDITIONAL INFORMATION-

Other:	No other health hazards are known.
Contains:	Synthetic base oils: Not expected to cause significant health effects under conditions of normal use, based on laboratory studies with the same or similar materials. Not mutagenic or genotoxic. Not sensitizing in test animals and humans. Additional information is available by request.



SYNMAX™ SYNTHETIC RACING OIL SAE 5W-50

Material Safety Data Sheet - Prepared According to OSHA Hazard Communication Standard 22CFR 1910.1200
Page 7 of 9 MSDS # 640550108 - Effective Date: 1JAN2009

IMDG EMS Spill:	Not applicable.	IMDG MFAG	Not applicable.
USCG Compatibility:	Not determined.	US DOT Bulk:	Not regulated.
US DOT Non-Bulk:	Not regulated.	DOT NAERG:	Not applicable.
TDG Bulk:	Not regulated.	TDG Non-Bulk:	Not regulated.
Mexico:	Not regulated.	Mexico Non-Bulk	Not regulated.

Review classification requirements before shipping materials at elevated temperatures.

SECTION 15

REGULATORY INFORMATION

-US FEDERAL REGULATIONS-

OSHA Classification:	Product when used for its intended purposes, is not hazardous according to the OSHA Hazard Communication Standard OSHA 29 CFR 1910.1200		
SARA Extremely Hazardous Substance:	This product does not contain greater than 1.0% of any chemical substance on the SARA Extremely Hazardous Substance List.		
SARA Section 313:	This product does not contain greater than 1.0% (greater than 0.1% for carcinogenic substance) of any chemical substances under SARA Section 313.		
SARA 311 Classifications:	Acute Hazard	(NO)	
	Chronic Hazard	(NO)	
	Fire Hazard	(NO)	
	Reactivity Hazard	(NO)	
SARA Toxic Release Inventory (TRI) 313:	Zinc compounds.	CERCLA Haz. Sub:	None Known.
FDA Approval:	Not Applicable.		

-STATE REGULATIONS-

This product is not regulated by California Prop 65 does not intentionally contain any chemicals known by the State of California to cause cancer and/or birth defects, New Jersey Right-to-Know Chemical List or Pennsylvania Right-to-Know Chemical List . However details on your regulation requirements you should contact the appropriate agency in your state.

-GLOBAL CHEMICAL INVENTORIES-

USA:	All components of this material are on the US TSCA Inventory or are exempt.
Other TSCA Regulations:	Section 4a (Nonane). May be subject to export notification under TSCA Sec.12(b).
EU:	This product requires notification under EC 7th Amendment Directive 92/32/EEC.
Japan:	This product may be imported to Japan only by Titan Japan.
Australia:	All component(s) of this product have been notified and assessed under the Industrial Chemicals (Notification and Assessment) Act, 1989. This product may only be imported by Titan Australia.
Canada:	All component(s) are in compliance with the Canadian Environment Protection Act and are present on the Domestic Substances List.
China:	This product requires notification before sale in China.

-PRODUCT REGISTRATIONS-

US Fuel Registration:	Not applicable.
US Dept of Agriculture:	This product has not been filed with the USDA to support H2 approvals.
NSF Nonfood Compounds:	This product has not been filed with the NSF to support H1 or H2 approvals.



SYNMAX™ SYNTHETIC RACING OIL SAE 5W-50

Material Safety Data Sheet - Prepared According to OSHA Hazard Communication Standard 29CFR 1910.1200
Page 8 of 9 MSDS # 640550108 - Effective Date: 1JAN2009

Finnish Registration No:	Not registered.	Swedish Registration No:	Not registered.
Norwegian Registration No:	Not registered.	Italian Registration No:	Not registered.
Korean Registration No:	Not registered.	New Zealand Registration:	Not registered.

-OTHER/INTERNATIONAL-

TDG Regulated Limit:	None known.
US Tariff Heading Number:	3403.19.50.00
Schedule B Number:	3403.19.0000

SECTION 16

LABEL INFORMATION

READ AND UNDERSTAND MATERIAL SAFETY DATA SHEET BEFORE HANDLING OR DISPOSING OF PRODUCT. THIS LABEL COMPLIES WITH THE REQUIREMENTS OF THE OSHA HAZARD COMMUNICATION STANDARD (29 CFR 1910.1200) FOR USE IN THE WORKPLACE. THIS LABEL IS NOT INTENDED TO BE USED WITH PACKAGING INTENDED FOR SALE TO CONSUMERS AND MAY NOT CONFORM WITH THE REQUIREMENTS OF THE CONSUMER PRODUCT SAFETY ACT OR OTHER REGULATORY REQUIREMENTS.

Product Code: 640550
Product Name: SYNMAX™ SYNTHETIC RACING OIL SAE 5W-50

ATTENTION: The following organs and/or organ systems may be damaged by over exposure to the material and/or its components. **PROLONGED OR REPEATED SKIN CONTACT MAY CAUSE OIL ACNE OR DERMATITIS. USED GASOLINE ENGINE AND OTHER SIMILAR TYPE OIL(S) HAS BEEN SHOWN TO CAUSE CANCER IN LABORATORY ANIMALS.**

Precautions: *Avoid prolonged or repeated contact with eyes, skin & clothing wash thoroughly after handling.*

FIRST AID

Inhalation: Remove victim to fresh air & provide oxygen if breathing is difficult. Get medical attention.
Skin Contact: Remove contaminated clothing and shoes and wipe excess from skin. Flush, wash and cleanse skin with soap and water. If irritation occurs, seek medical attention. Do not reuse clothing until cleansed.
Eye Contact: Flush with water. If irritation occurs, seek medical attention.
Ingestion: Do not induce vomiting. In general, no treatment is necessary unless large quantities of product are ingested. However, seek medical attention.

FIRE

In case of fire: Use water fog, 'alcohol foam', dry chemical or carbon dioxide (CO₂) to extinguish flames. Do not use a direct stream of water. Material will float & can be re-ignited on surface of water.

SPILL OR LEAK

Dike & Contain Spill.
FOR LARGE SPILLS: Remove with vacuum truck or pump to storage container/salvage vessels.

FOR SMALL SPILLS: Soak up residue with an absorbent such as clay, sand or other suitable material. Place in container and seal tightly for proper disposal.

CONTENTS: Synthetic hydrocarbon base oil, Mixture; Proprietary additives, Mixture;



SYNMAX™ SYNTHETIC RACING OIL SAE 5W-50

Material Safety Data Sheet - Prepared According to OSHA Hazard Communication Standard 29CFR 1910.1200
Page 9 of 9 MSDS # 640550108 - Effective Date: 1JAN2009

NFPA Rating: Zinc Dialkyldithiophosphate 68649-42-3
(Health, Fire, Reactivity): 0, 1, 0

TRANSPORTATION

US Department of Transportation Classification

This Material is not subject to DOT regulations under section 49 CFR Parts 171-180.

Oil: This product is an oil under 49CFR (DOT) Part 130. If shipped by rail or highway in a tank with a capacity of 3500 gallons or more, it is subject to these requirements. Mixtures or solutions containing 10% or more of this product may also be subject to this rule.

CAUTION: Misuse of empty containers can be hazardous. Empty containers can be hazardous if used to store toxic, flammable, or reactive materials. Cutting or welding of empty containers might cause fire, explosion or toxic fumes from residues. Do not pressurized or expose to open flames or heat. Keep container closed and drum seal in place.

Name and Address: **TITAN PERFORMANCE PRODUCTS, LLC, 13750 METRIC DRIVE, ROSCOE, IL 61073 USA**

Revisions: This MSDS has no revisions since 1 January 2009

SECTION 17	ADMINISTRATIVE INFORMATION AND DECLARATIONS
Manufacturer Address:	Titan Performance Products, LLC. 13750 Metric Dr Roscoe IL 61073

Users Responsibility/Disclaimer of Liability:

It is the user's responsibility to satisfy itself that the product is suitable for the intended use. The information and recommendations contained in this MSDS document are offered for the user's consideration and examination. Information is based on the data available to Titan Performance Products, LLC. at this time, and is believed to be accurate. MSDS Information is provided independently of any sale of the product, for purpose of hazard communication; with the intent to describe the product solely with respect to health, safety and the environment. Appropriate warnings and safe-handling procedures should be provided to handlers and users.

This document must not be interpreted as a guarantee of any specific property of the product. In no event shall Titan Performance Products, LLC. be responsible for damages of any nature(s), whatsoever resulting from the use or reliance of information. No representation or warranty, either expressed or implied, of merchantability or fitness for a particular purpose is made with respect to information of the product to which the information refers.

MSDS information contained herein is not intended to constitute product performance. You are urged to obtain the product data sheet. You shall be solely responsible for deciding whether said MSDS information is suitable and beneficial for all products you buy, process, use or distribute, and are encouraged to advise those who come in contact with such products of the information contained herein. If buyer repackages this product, it is the user's responsibility to insure proper health, safety & other necessary information is included with and/or on the container.

To determine the applicability of effect of any law or regulation with respect to the product, you should consult with your legal advisor or the appropriate government agency. Titan Performance Products, LLC. will not provide advice on such matters, or be responsible for any injury from the use of the product described herein. Alteration of this document is strictly prohibited. Except to the extent as required by law, re-publication or retransmission of this document, in whole or in part, is not permitted, without the expressed written consent of Titan Performance Products, LLC.